
# Silica gel for Column Chromatography





Spherical Silica gel for Preparative LC
Column Chromatography
Flash Chromatography




# **Spherical Silica gel for Column Chromatography**



Spherical silica gel are superior to irregular shaped silica gel in gel sedimentation, and form more uniform column beds. They have begun to be in wide use for laboratory-scale purification to industrial-scale preparative work.

## **Advantages of Spherical Silica gel as Compared to Irregular shaped**



## **Selection Guide for Preparative Chromatography**

#### pH of Silica Gel

Pure silica gel (SiO<sub>2</sub>) is known to be a weak acid from its surface structure. In instances where samples are unstable under acidic conditions, pure silica gel may

not be suited for their separation. Our pH-adjusted material, Silicagel 60N, are ideal in separating a wide range of compounds.

#### **Particle Size**

	Particle size	Characteristics		
Flash Chromatography	40~ 50 μ m	Loose material for high-resolution, flash chromatography. Due to narrow particle size distribution, easily prepare column beds with superior in resolution, permeability and uniformity. Suitable for purification of target substances in complex matrix. Useful as loose material for medium-pressure preparative columns.		
	40∼ 100 µ m	Loose material for standard flash chromatography. Due to hig permeability, usable under hydrostatic pressure, depending o eluents. Useful as fillers for high-resolution, small-scale ope columns.		
Column Chromatography	63~ 210 µ m	Economical material for open column chromatography, having the advantage of easy handling and high cost performance Suitable for rough purification. Contribute greatly to reduction in purification cost in a large-scale preparative operation.		
	100∼ 210 µ m	Loose material for standard open column chromatography. Form uniform beds even in large columns. Suitable for mass preparative chromatography treatment by overload technique. Due to high permeability and increased throughput, enhances productivity.		

# **Spherial Silica gel for Column Chromatography**

## **Comparison of Resolution**

The separating ability of our spherical Silicagel was compared with that of irregular shaped silica gel with a similar particle size. The spherical silica gels are expected to enhance resolution and reproducibility because they are able to form more uniform column beds.

#### **Chromatographic conditions**

## Column : stainless steel, length 250mm, inner diameter 10mm


Mobile phase : *n*-Heptane Flow rate : 2.5mL/min


 $Temperature: Room\ temperature$ 

Detection : UV 254nm Amount of Injection :  $50 \mu L$  Sample : 1. Benzene 0.5 mg/mL 2. Naphthalene 0.05 mg/mL


3. Biphenyl 0.015 mg/mL


#### **Products For Flash Chromatography**






#### **Products For Column Chromatography**





### **Particle Size Distribution of Spherical Silicagel**



# **Ordering information**

Product Name	Silicagel 60 (Spherical)				Silicagel 60N (Spherical, Neutral)			
pH (10% sus.)	6.0 ± 1.0 (Acidic)				7.0 ± 0.5 (Neutral)			
Particle size ( µ m)	For flash For column chromatography		For flash chromatography		For column chromatography			
Cat.No. Pack size	40~50	40~100	63~210	100~210	40~50	40~100	63~210	100~210
1kg	37562-79	37559-79	37564-79	37558-79	37563-79	37561-79	37565-79	37560-79
10kg	37562-84	37559-84	37564-84	37558-84	37563-84	37561-84	37565-84	37560-84
25kg	37562-85	37559-85	37564-85	37558-85	37563-85	37561-85	37565-85	37560-85

# **Physical Properties of Silica gel**

Product Name	Silicagel 60 (Spherical)	Silicagel 60N (Spherical, Neutral)
pH (10% sus.)	$6.0 \pm 1.0$ (Acidic)	7.0 ± 0.5 (Neutral)
Specific surface area	$700 \pm 50$ m <sup>2</sup> /g	$650 \pm 50$ m <sup>2</sup> /g
Pore diameter	$65 \pm 10$	60 ± 10
Pore volume	$1.15 \pm 0.10 \text{ mL/g}$	$0.90 \pm 0.10 \text{ mL/g}$
Bulk density	$0.40 \pm 0.05 \text{ g/mL}$	$0.50 \pm 0.05 \text{ g/mL}$
Water content	15.0 %	15.0 %
Cl	100 ppm	100 ppm
Na	100 ppm	100 ppm
Mg	50 ppm	50 ppm
Ca	50 ppm	500 ppm
Al	150 ppm	150 ppm
Ti	150 ppm	150 ppm
Fe	50 ppm	50 ppm



11-5, Nihonbashi-Honcho 3-chome, Chuo-ku, Tokyo 103-0023 Japan

Telephone +813-3639-8301 Telefax +813-3639-9435 http://www.kanto.co.jp e-mail: reag-info@gms.kanto.co.jp